

# SOUTHERN TRUCK

Lift your life.

**2007-2014 Wrangler  
1.5" Wheel Spacers**

# 95004

2 - 1 1/2" 5-Lug Wheel Spacers      5 - Lug nuts

## PRE-INSTALLATION

**Professional installation by a certified technician is strongly recommended.**

*Not responsible for altered products. No claims are made regarding any lifting devices. Any and all claims implied in this document excluded.*

### NOTES:

Check spacers regularly to ensure tightness.

### REQUIRED TOOLS:

Floor Jack

Jack Stands

Torque Wrench

19mm Socket

Flat Screwdriver

## INSTALLATION INSTRUCTIONS

**STEP 1:** Chock tires to avoid vehicle roll. Jack up vehicle so that wheels are just off the ground.

**STEP 2:** Remove all lug nuts. (19mm Socket)

**STEP 3:** Remove wheels/tires.

**STEP 4:** Check for factory retaining star washer and remove if present. Wheel spacer must sit flat against the rotor. Vibrations may occur if washers are not removed from wheel studs.

**STEP 5:** Install wheel spacers on studs. Secure with supplied lug nuts and tighten to factory specs. (Torque wrench) **DO NOT OVERTIGHTEN**

**STEP 6:** Re-install wheels/tires.

**STEP 7:** Re-install factory lug nuts and tighten to factory specs. (Torque wrench) **DO NOT OVERTIGHTEN**

## POST-INSTALLATION

### MAINTENANCE:

Make sure included lug nuts are long enough to sit tight against the wheel - if not, replace with longer lug nuts.

Re-tighten lug nuts after 500 Miles.

Wheel lug nuts should be re-tightened to factory torque specs. periodically. Always inspect components and re-tighten lug nuts during routine service.